

Toppers

Flemings are one of the largest manufacturers of Grass Toppers in the UK and Ireland with over 20 years experience manufacturing this range of product, having developed the widest range of rotary pasture toppers on the market to suit the needs of hobby, equestrian and grassland farmers, parkland maintenance, airports and sports pitches.

Fleming grass toppers are fitted with specially sourced convex skids for reduced friction and minimal ground marking, are designed for low cost maintenance with shear bolt protection against shock loading to ensure longer life.

All Fleming Toppers are manufactured from high quality steel ensuring a longer working lifespan, are fitted with easy access grease points where necessary and undergo a 5 stage cleaning and painting process culminating in oven curing for better protection against the varied climatic conditions. Experience over the past 20 years has proven that Fleming Toppers manufactured from high quality steel and cared for with annual maintenance will have a life span in excess of 15 years, offering a very low annual pasture management cost. Flemings offer a range of in-line, semi-offset and fully off-set Toppers to suit all grass topping requirements.



Toppers

In-line and Semi Offset



- Reinforced one piece fabricated deck from 3mm steel plate.
- Reinforced structural frame across the body of the topper for absolute rigidity.
- Cat. 1 pins on models; TOP3, TOP4, TOP5.
- Cat.1 & Cat.2 pins on TOP6
- Galvanised headstock and skids for longer life
- Double jaw support lift arm brackets on TOP6
- Adjustable headstock for In-Line and Semi-Offset on TOP3, TOP4 and TOP5 models.
- Heavy Duty Comer Gearbox
- Boron steel blade carrier.
- Shear bolt protected PTO shaft.
- Convex skids
- Wheel option available for TOP4 and TOP5.

Code	TOP3	TOP4	TOP5	TOP6
Tractor HP Req'd	20	20	30	40
Transport Width	1.17m	1.4m	1.65m	1.82m
No. of Rotors	1	1	1	1
No. of Blades	2	2	2	2
No. of Gearbox	1	1	1	1
Gearbox Rating	30hp	30hp	30hp	40hp
Weight	170kg	202kg	246kg	323kg

Toppers

In-line Topper



- TOP9 – 9ft standard model for topping meadows and grass.
- Fabricated one piece deck from 3mm steel plate.
- Reinforced structural frame across the the body of the topper for absolute rigidity.
- H.D galvanised chain support for secure transport
- Galvanised headstock, guards and skids.
- Floating headstock for constant ground contact and even cut.
- Reinforced 4mm sides with convex skids
- Indestructible HD boron steel blade carriers with harden steel blades
- Gearbox and rotors mounted on a one piece heavy duty central base plate
- HD 55h.p Comer gear box with straight drive-line protected by rubber couplings
- PTO over-run and shear bolt protection against rotor impact
- Double jaw support lift arm brackets.
- Cat 2 lift arm pins.

Super 900 model

TOP9INHD (2.7m) 9ft Heavy Duty model

(For rushes and Heavy Grass)

- Fitted with 75HP gear boxes.
- Heavy duty flexible knuckle drive line protected by rubber couplings.
- Fitted with fluted blades with additional straight blades for mulching effect when cutting.

Code	HP	Transport Width	Rotors	Blades	Gearbox	Gearbox Rating	Weight
TOP9	70	2.74m	2	4	3	55hp	494kg
TOP9INHD	80	2.74m	2	8	3	75hp	500kg

Super Float Grass Topper

TOP6SM (1.8m) 6ft Single rotor
For meadows and grass



- 5 stage painting and heat treatment process.
- Fabricated one piece deck from 3mm steel plate fitted on reinforced structural frame across the body of the topper for absolute rigidity.
- Floating top link and hinged body provide bi-lateral movement for constant ground contact and even cut.
- Reinforced 4mm sides with convex skids
- Gearbox and rotor mounted on a heavy duty central base plate
- Single rotor with indestructible HD boron steel blade carrier fitted with free floating Specially designed fluted hardened steel cutting blades to disperse grass evenly
- Adjustable cutting height 50mm – 200mm
- Converts to working/transport position manually
- Comer gear boxes with straight drive-line.
- PTO over-run and shear bolt protection against rotor impact
- Double jaw support lift arm brackets.
- Cat 2 lift arm pins.
- Easy access greasing points
- Parking stand

Code	HP	Transport Width	Rotors	Blades	Gearbox	Gearbox Rating	Weight
TOP6SM	50	1.82m	1	2	2	40hp	431kg

Toppers

Super Float Grass Topper

Super Float Grass Topper (Standard models)

For meadows and grass

TOP7SF (2.14m) 7ft Twin Rotor
TOP8SF (2.5m) 8ft Twin Rotor



- Fabricated one piece deck from 3mm steel plate fitted on reinforced structural frame along the body of the topper for absolute rigidity.
- Floating top link and hinged body provide bi-lateral movement for constant ground contact and even cut.
- Counter rotation of Twin rotor with Indestructible boron steel blade carriers fitted with free floating boron steel fluted blades lift and disperse the grass evenly.
- Adjustable cutting height 50mm – 200mm
- Converts to working/transport position hydraulically, with spring loaded safety latch when in transport position.
- Hydraulic breakaway standard for the ultimate machine protection and speed of operation. (can be reset from the tractor seat)
- Comer gear boxes with straight drive-line protected by rubber couplings
- PTO over-run and shear bolt protection against rotor impact
- Double jaw support lift arm brackets.
- Cat 2 lift arm pins.

TOP8SFHD (2.5m) 8ft Twin Rotor (Heavy Duty model)

For rushes and heavy grass

- Fitted with 75HP gear box.
- Heavy duty flexible knuckle drive line protected by rubber couplings.
- Fitted with fluted blades with additional straight blades for mulching effect when cutting.

Code	HP	Transport Width	Rotors	Blades	Gearbox	Gearbox Rating	Weight
TOP7SF	70	1.83m	2	4	3	55hp	616kg
TOP8SF	80	1.83m	2	4	3	55hp	650kg
TOP8SFHD	80	1.83m	2	8	3	75hp	670kg

Toppers

Super Float Grass Topper TOP10SF



- Manufactured from high tensile strength steel resulting in a light weight yet durable machine
- Floating top link and hinged body provide bi-lateral movement for constant ground contact and even cut.
- Counter rotation of triple rotor with Indestructible boron steel blade carriers fitted with free floating boron steel fluted blades lift and disperse the grass evenly.
- Adjustable cutting height 50mm – 200mm
- Converts to working/transport position hydraulically, with spring loaded safety latch when in transport position.
- Hydraulic breakaway standard for the ultimate machine protection and speed of operation. (can be reset from the tractor seat)
- Comer gear boxes with straight drive-line protected by rubber couplings
- PTO over-run and shear bolt protection against rotor impact
- Double jaw support lift arm brackets.
- Cat 2 lift arm pins.
- Protective Curtain

Code	HP	Transport Width	Rotors	Blades	Gearbox	Gearbox Rating	Weight
TOP10SF	100	1.65m	3	6	4	55hp	700kg

Toppers

Trailed Superfloat Grass Topper

The Fully-Offset trailed Grass Topper was designed with the more professional operator in mind, for use on parkland, sports fields, airports, equestrian and agricultural use. The award winning design with the unique spring assisted free floating movement allows the cutting deck to stay in constant contact with the ground while the counter rotation combine with the fluted blades creating an up-draught lifting the grass to leave a smooth even cut. All Fleming Toppers have indestructible boron steel rotors with free floating blades for better collision protection. Ideal for outlying farms with undulating land where a low HP requirement is beneficial and road transport is necessary.

There are 2 models available;
TOP8T 2.5m 8ft Standard.
TOP9T 2.7m 9ft Heavy Duty



TOP8T – 2.5m 8ft Standard **For meadow and grass**

- 5 stage painting and heat treatment process.
- Fabricated one piece deck from 3mm steel plate fitted on a reinforced structural frame of the topper for absolute rigidity.
- Guards and skids galvanised and bolted in place for quiet operation and easy maintenance.
- Free floating deck with spring assisted floatation allowing the deck to glide over the ground keeping the blades at an even cutting height at all times, creating minimal stress on the machine
- Reinforced heavy duty 4mm sides with convex skids.
- Counter rotation of the rotors combine with the specially designed fluted hardened steel cutting blades to disperse grass evenly
- Gearboxes and twin rotors mounted on a heavy duty one piece central base plate and fitted with Indestructible boron steel blade carriers with free floating blade protection in the event of a collision.

Toppers

Trailed Superfloat Grass Topper



- Adjustable cutting height 50mm – 200mm
- Converts to working/transport position hydraulically, follows directly behind the tractor.
- All pivot points are heavy duty and fitted with easy access grease points.
- Comer gear box with straight drive-line protected by rubber couplings.
- Lift arm draw-bar combined with Wide Angle PTO c/w over-run and shear bolt protection for better manoeuvrability and tighter turning when operating.
- Oversized tyres (10.5 x 75 x 15.3) on a reinforced wheel carriage
- Parking stand

TOP9T 2.7m 9ft Heavy Duty

- Fitted with 75HP gear box.
- Heavy duty flexible knuckle drive line protected by rubber couplings.
- Fitted with fluted and additional straight blades for mulching effect when cutting.
- Ideal for large farms, contract work and hire fleets.
- Hydraulic safety locking mechanism

Code	HP	Transport Width	Rotors	Blades	Gearbox	Gearbox Rating	Weight
TOP8T	80	2.53m	2	4	3	55hp	650kg
TOP9T	80	2.80m	2	8	3	75hp	850kg

Toppers

Heavy Duty 6ft Toppers

For rushes and heavy grass/weeds
TOP6HD.

- Heavy Duty Semi-Offset Grass Topper (6ft)
- Cat 2 pins
- Used for the clearance of heavy rushes and bracken.
- 80HP Gear Box
- Friction Clutch or shear bolt option
- Heavy Duty reinforced Deck
- Heavy Duty Boron steel blade carrier with high performance blades
- Galvanised skids and A frames
- Smooth top deck (no water traps)



Code	HP	Transport Width	Rotors	Blades	Gearbox	Gearbox Rating	Weight
TOP6HD	90	1.8m	1	4	1	80hp	382kg