

Aerators

5ft Model (AR5)



- Weight carrying rack
- Heavy duty galvanized frame complete with parking stands
- Chain harrow towing eye fitted
- Heavy duty three point linkage
- Blades fitted on a spiralled effect for smooth effective operation.
- Heavy duty 45mm bearings
- Bearing protective skids
- Unique Blade Locking system.
- Replaceable chamfered boron steel blades fitted in positive location socket resulting in less stress on bolts to keep blades tight.
- Double sided blade for easy ground entry and exit for minimal surface damage (250mm by 8mm)
- Fitted concrete weights optional



Model	AR5
working width (M)	1.5
Rotor angle adjustment	0-10°
HP Requirement	30hp
Unladen Weight (KG)	235kg
Number of blades	24

Aerators

8ft (AR8) & 10ft (AR10) models



- Weight carrying rack
- Heavy Duty frame
- Parking stands
- Chain harrow towing eye fitted
- Adjustable rotor angle
- Heavy duty three point linkage
- Blades fitted on a spiralled effect for smooth effective operation.
- Heavy duty 45mm bearings
- Bearing protective skirts
- Unique Blade Locking system.
- Replaceable chamfered boron steel blades fitted in positive location socket resulting in less stress on bolts to keep blades tight. (250mm by 10mm)
- Fitted concrete weights optional



Model	AR8	AR10
working width (M)	2.5	3
Rotor angle adjustment	0-10°	0-10°
HP Requirement	50	70
Unladen Weight (KG)	415	518
Number of blades	42	48

Aerators

5m - 16ft Folding Aerator (AR16)



- Weight carrying rack (Optional concrete weights)
- High performance working capacity – compact transport position.
- Heavy duty rams for smooth hydraulic folding mechanism.
- Rubber cushions on transport wings for smooth, quiet transport.
- Lock down wing mechanism for consistent even penetration.
- Chain harrow towing eye fitted
- Adjustable positional rotor angle up to 10 degrees.
- Heavy duty three point linkage
- Blades fitted on a spiralled effect for smooth effective operation.
- Heavy duty 45mm bearings
- Bearing protective skirts
- Unique Blade Locking system.
- Replaceable chamfered boron steel blades fitted in positive location socket resulting in less stress on bolts to keep blade tight. (250mm by 10mm)



Model	AR16
working width (M)	5
Rotor angle adjustment	0–10°
HP Requirement	100+
Unladen Weight (KG)	1015kg
Number of blades	84
Transport Width (M)	2.67

